FRSC Chemical Solutions

SAFETY DATA SHEET

1. Identification

Product identifier Gunk Brake Parts Cleaner - Non Chlorinated

Other means of identification

SDS number M705 Part No. M705

Tariff code 3814.00.5090

Recommended use Brake Cleaner
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company nameRSC Chemical SolutionsAddress600 Radiator Road

Indian Trail, NC 28079

United States

Telephone Customer Service:

Customer Service: (704) 821-7643 Technical: (704) 684-1811

Website www.rscbrands.com

E-mail Not available.

Emergency phone number Emergency Telephone: (303) 623-5716

Emergency Contact: RMPDC (877-740-5015)

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsAcute toxicity, oralCategory 3Acute toxicity, dermalCategory 3Skin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2A

Serious eye damage/eye irritation Category 2/2
Reproductive toxicity Category 2
Specific target organ toxicity, single exposure Category 1

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

exposure

Environmental hazards Hazardous to the aquatic environment, acute Category 1

hazard

Hazardous to the aquatic environment, Category 1

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Toxic if swallowed. Toxic in contact with skin. Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Category 1

Material name: Gunk Brake Parts Cleaner - Non Chlorinated M705 Version #: 01 Issue date: 04-23-2015

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If

inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed: Call a poison center/doctor. If exposed or concerned: Get medical advice/attention. Rinse mouth. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off immediately all contaminated clothing

and wash it before reuse. Collect spillage.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

not otherwise None known.

Supplemental information 65% of the mixture consists of component(s) of unknown acute oral toxicity. 65% of the mixture consists of component(s) of unknown acute dermal toxicity. 40% of the mixture consists of

component(s) of unknown acute dermal toxicity. 40% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 40% of the mixture consists

of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Heptane		142-82-5	50 - < 60
METHANOL		67-56-1	30 - < 40
Carbon Dioxide		124-38-9	10 - < 20
2-PROPANONE		67-64-1	5 - < 10

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contactTake off immediately all contaminated clothing. Wash with plenty of soap and water. Get medical

advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting without

advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device.

Most important symptoms/effects, acute and

delayed

General information

Indication of immediate medical attention and special treatment needed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

under observation. Symptoms may be delayed.

Take off immediately all contaminated clothing. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Powder. Alcohol resistant foam. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2-PROPANONE (CAS 67-64-1)	PEL	2400 mg/m3
,		1000 ppm

US. OSHA Table Z-1 Limit Components		уре	•	alue	
Carbon Dioxide (CAS 124-38-9)	Р	EL		000 mg/m3	
(040 440 00 5)	_			000 ppm	
Heptane (CAS 142-82-5)	Р	EL		000 mg/m3 00 ppm	
METHANOL (CAS 67-56-1)	D	'EL		60 mg/m3	
WETTANOL (CAS 07-50-1)	Г	CL .		00 ppm	
US. ACGIH Threshold Lim	it Values			· · · · · ·	
Components		уре	Va	alue	
2-PROPANONE (CAS 67-64-1)		TEL		50 ppm	
		WA		00 ppm	
Carbon Dioxide (CAS 124-38-9)	S	TEL	30	0000 ppm	
		WA		000 ppm	
Heptane (CAS 142-82-5)	_	TEL		00 ppm	
		WA		00 ppm	
METHANOL (CAS 67-56-1)		TEL		50 ppm	
	Т	WA	20	00 ppm	
US. NIOSH: Pocket Guide Components		ds ype	Va	alue	
2-PROPANONE (CAS	Т	WA	59	00 mg/m3	
67-64-1)			26	50 ppm	
Carbon Dioxide (CAS	S	TEL		1000 mg/m3	
124-38-9)			3(0000 ppm	
	т	WA		000 ppm 000 mg/m3	
	'	VVA		000 mg/m3	
Heptane (CAS 142-82-5)	C	eiling		300 mg/m3	
110010110 (0710 112 02 0)		.og		10 ppm	
	Т	WA		50 mg/m3	
			85	5 ppm	
METHANOL (CAS 67-56-1)	S	TEL		25 mg/m3	
				50 ppm	
	Т	WA		60 mg/m3	
			20	00 ppm	
ogical limit values					
ACGIH Biological Exposu	re Indices				
Components	Value	Determinant	Specimen	Sampling Time	
2-PROPANONE (CAS 67-64-1)	50 mg/l	Acetone	Urine	*	
METHANOL (CAS 67-56-1)	-	Methanol	Urine	*	
* - For sampling details, plea	ase see the source	document.			
osure guidelines					
US - California OELs: Skir	-				
METHANOL (CAS 67-5	56-1)	Can	be absorbed throu	igh the skin	

Can be absorbed through the skin.

Can be absorbed through the skin.

Material name: Gunk Brake Parts Cleaner - Non Chlorinated M705 Version #: 01 Issue date: 04-23-2015

US ACGIH Threshold Limit Values: Skin designation

US - Tennessee OELs: Skin designation

METHANOL (CAS 67-56-1)

METHANOL (CAS 67-56-1)

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

METHANOL (CAS 67-56-1)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eve wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Chemical respirator with organic vapor cartridge and full facepiece. Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Clear. Liquid. **Appearance**

Liquid. **Physical state Form** Aerosol. Color Colorless

Odor Hydrocarbon like Not available. **Odor threshold** Not available. На

-144.04 °F (-97.8 °C) estimated Melting point/freezing point Initial boiling point and boiling -109.3 °F (-78.5 °C) estimated

range

-4.0 °F (-20.0 °C) estimated Flash point

Evaporation rate Not available. Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits 2.6 % estimated

Flammability limit - lower (%)

Flammability limit - upper

36 % estimated

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%)

Vapor pressure 6539.44 hPa estimated

Not available. Vapor density Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

464 °F (240 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. **Viscosity** Not available.

Other information

6.09 lbs/gal estimated Density

Explosive properties Not explosive. Flammability class Flammable IA estimated
Heat of combustion (NFPA 29.64 kJ/g estimated

30B)

Oxidizing properties

Percent volatile

Specific gravity

VOC (Weight %)

Not oxidizing.

35 % estimated

0.73 estimated

85 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

Hazardous polymerization does not occur.

reactions

Conditions to avoid Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Aluminum.

Hazardous decomposition No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs by inhalation. May cause damage to organs through prolonged or

repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea,

vomiting.

Skin contact Toxic in contact with skin. Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Toxic if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

cause redness and pain.

Information on toxicological effects

Acute toxicity Toxic in contact with skin. Toxic if swallowed. Narcotic effects.

Components	Species	Test Results
2-PROPANONE (CAS 67-64-1)		

Acute

Dermal

LD50 Rabbit 20000 mg/kg 20 ml/kg

Inhalation

LC50 Rat 76 mg/l, 4 Hours

50.1 mg/l, 8 Hours

Oral

LD50 Mouse 3000 mg/kg

 Rabbit
 5340 mg/kg

 Rat
 5800 mg/kg

Heptane (CAS 142-82-5)

Acute

Inhalation

 LC50
 Rat
 103 mg/l, 4 Hours

 LD50
 Mouse
 75 mg/l, 2 Hours

Material name: Gunk Brake Parts Cleaner - Non Chlorinated M705 Version #: 01 Issue date: 04-23-2015

Components	Species	Test Results
METHANOL (CAS 67-56-1)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	15800 mg/kg
Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours
	Rat	64000 ppm, 4 Hours
		87.5 mg/l, 6 Hours
Oral		
LD50	Dog	8000 mg/kg
	Monkey	2 g/kg
	Mouse	7300 mg/kg
	Rabbit	14.4 g/kg
	Rat	5628 mg/kg
* Estimates for product ma	ay be based on additional component data not s	hown.
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye rritation	Causes serious eye irritation.	

Not a respiratory sensitizer. Respiratory sensitization

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity -

single exposure

Causes damage to organs. May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be **Chronic effects**

harmful.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Components		Species	Test Results		
2-PROPANONE (CAS	2-PROPANONE (CAS 67-64-1)				
Aquatic					
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours		
Heptane (CAS 142-82	-5)				
Aquatic					
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours		

Species Test Results Components

METHANOL (CAS 67-56-1)

Aquatic

> 10000 mg/l, 48 hours EC50 Water flea (Daphnia magna) Crustacea Fish LC50 Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-PROPANONE -0.244.66 Heptane **METHANOL** -0.77

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

> under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN1950 **UN number**

UN proper shipping name

AEROSOLS

Transport hazard class(es)

ORM-D Class

Subsidiary risk Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

306 Packaging exceptions Packaging non bulk 302, 304 Packaging bulk 302, 314, 315

IATA

UN1950 **UN number** UN proper shipping name **AEROSOLS**

Transport hazard class(es)

2

Class Subsidiary risk

Packing group Not applicable.

Environmental hazards Yes 21 **ERG Code**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

^{*} Estimates for product may be based on additional component data not shown.

Other information

Passenger and cargo Allowed.

aircraft

Cargo aircraft only Allowed.

IMDG

UN1950 **UN** number **AEROSOLS** UN proper shipping name

Transport hazard class(es)

Class 2 Subsidiary risk

Packing group Not applicable.

Not established.

Environmental hazards

Marine pollutant Yes F-D, S-U

EmS

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

IATA; IMDG



Marine pollutant



General information IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-PROPANONE (CAS 67-64-1) Listed. Heptane (CAS 142-82-5) Listed. METHANOL (CAS 67-56-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
METHANOL	67-56-1	30 - < 40	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

METHANOL (CAS 67-56-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

2-PROPANONE (CAS 67-64-1)

6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

2-PROPANONE (CAS 67-64-1)

35 %WV

DEA Exempt Chemical Mixtures Code Number

2-PROPANONE (CAS 67-64-1) 6532

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

2-PROPANONE (CAS 67-64-1)

METHANOL (CAS 67-56-1)

US. Massachusetts RTK - Substance List

2-PROPANONE (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9)

Heptane (CAS 142-82-5)

METHANOL (CAS 67-56-1)

US. New Jersey Worker and Community Right-to-Know Act

2-PROPANONE (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9)

Heptane (CAS 142-82-5)

METHANOL (CAS 67-56-1)

US. Pennsylvania Worker and Community Right-to-Know Law

2-PROPANONE (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9)

Heptane (CAS 142-82-5)

METHANOL (CAS 67-56-1)

US. Rhode Island RTK

2-PROPANONE (CAS 67-64-1)

METHANOL (CAS 67-56-1)

US. California Proposition 65

M705 Version #: 01 Issue date: 04-23-2015

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm

US - California Proposition 65 - CRT: Listed date/Developmental toxin

METHANOL (CAS 67-56-1) Listed: March 16, 2012

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 04-23-2015

Version # 01

HMIS® ratings Health: 4*

Flammability: 4 Physical hazard: 0

NFPA ratings Health: 4

Flammability: 4 Instability: 0

NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).