ASHLAND	Page: 1
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 12/4/2015
	SDS Number: R0171982
All-Climate™ SAE 20W-50 MOTOR OIL	Version: 1.0
130	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name

: All-Climate[™] SAE 20W-50 MOTOR OIL

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-ASHLAND (1-800-274-5263)
Ashland	
P.O. Box 2219	Regulatory Information Number
Columbus, OH 43216	1-800-325-3751
United States of America	
	Product Information
	614-790-3333
EHS Customer Requests@ashland.com	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
Benzenesulfonic acid, C10-60- alkyl derivs., sodium salts	90194-32-4	Eye Irrit. 2A; H319	6.22

ASHLAND	Page: 2
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 12/4/2015
	SDS Number: R0171982
All-Climate™ SAE 20W-50 MOTOR OIL	Version: 1.0
130	

SECTION 4. FIRST AID MEASURES

General advice	: No hazards which require special first aid measures.
If inhaled	 If breathed in, move person into fresh air. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	: Remove contact lenses. Protect unharmed eye.
If swallowed	 Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: No symptoms known or expected.
Notes to physician	: No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	carbon dioxide and carbon monoxide Hydrocarbons
Specific extinguishing methods	:	
		Product is compatible with standard fire-fighting agents.
Further information	:	Standard procedure for chemical fires.
Special protective equipment	:	In the event of fire, wear self-contained breathing apparatus.

ASHLAND	Page: 3
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 12/4/2015
	SDS Number: R0171982
All-Climate [™] SAE 20W-50 MOTOR OIL	Version: 1.0
130	

for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.	
Environmental precautions	: Prevent further leakage or spillage if safe to do so.	
Methods and materials for containment and cleaning up	 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. 	
Other information	: Comply with all applicable federal, state, and local regulations.	

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. 	
Conditions for safe storage	: Electrical installations / working materials must comply with the technological safety standards.	I
Materials to avoid	: No materials to be especially mentioned.	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Engineering measures	: General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye protection	:	Not required under normal conditions of use. Wear splash- proof safety goggles if material could be misted or splashed into eyes.

ASHLAND		Page: 4
SAFETY DATA SHEET	Revision Da	ate: 05/22/2015
	Print	Date: 12/4/2015
	SDS Nur	nber: R0171982
All-Climate [™] SAE 20W-50 MOTOR OIL		Version: 1.0
130		

Skin and body protection	 Wear as appropriate: Safety shoes Wear resistant gloves (consult your safety equipment supplier).
Hygiene measures	: General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	liquid
Colour	:	amber
Odour	:	hydrocarbon-like
Odour Threshold	:	No data available
рН	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 390 °F / > 199 °C Method: Cleveland open cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit	:	6 %(V) Calculated Explosive Limit
Lower explosion limit	:	
Vapour pressure	:	0.0133333 hPa (21.11 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8834 g/cm3 (15.56 °C)
Solubility(ies) Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Thermal decomposition	:	

ASHLAND	Page: 5
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 12/4/2015
	SDS Number: R0171982
All-Climate [™] SAE 20W-50 MOTOR OIL	Version: 1.0
130	

	No data available
Viscosity Viscosity, dynamic	: No data available
Viscosity, kinematic	: 171 mm2/s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	No decomposition if stored and applied as directed.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	Product will not undergo hazardous polymerization.
Incompatible materials	Strong oxidizing agents
Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of	:	Inhalation
exposure		Skin contact
		Eye Contact
		Ingestion

Acute toxicity

Not classified based on available information. **Skin corrosion/irritation** Not classified based on available information. <u>Product:</u> Result: Repeated exposure may cause skin dryness or cracking.

Components:

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts: Result: Not irritating to skin

Serious eye damage/eye irritation

Not classified based on available information. <u>Product:</u> Remarks: Unlikely to cause eye irritation or injury.

ASHLAND	Page: 6
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 12/4/2015
	SDS Number: R0171982
All-Climate [™] SAE 20W-50 MOTOR OIL	Version: 1.0
130	

Components:

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts: Result: Irritating to eyes

Respiratory or skin sensitisation Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information. Germ cell mutagenicity Not classified based on available information. Carcinogenicity Not classified based on available information. **Reproductive toxicity** Not classified based on available information. STOT - single exposure Not classified based on available information. STOT - repeated exposure Not classified based on available information. Aspiration toxicity Not classified based on available information. Product:

No aspiration toxicity classification

Further information Product:

Remarks: No data available

Carcinogenicity: IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity No data available Persistence and degradability No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

ASHLAND	Page: 7
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 12/4/2015
	SDS Number: R0171982
All-Climate [™] SAE 20W-50 MOTOR OIL	Version: 1.0
130	

Other adverse effects

No data available

Product:

Additional ecological	:	No data available
information		

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Net departque geode
Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

ASHLAND	Page: 8
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 12/4/2015
	SDS Number: R0171982
All-Climate™ SAE 20W-50 MOTOR OIL	Version: 1.0
130	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

no

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312	2 Hazards : No SARA Hazards				
SARA 313 Component(s)	Component(s)SARA 313 known CAS numbers that		ain any chemical components with exceed the threshold (De Minimis) I by SARA Title III, Section 313.		
Pennsylvania	Right To Know				
	HEAVY PARAF	· ⊢ Iſ	NIC DISTILLATE	64742-54-7	90.00 - 100.00 %
	Benzenesulfoni sodium salts	сa	acid, C10-60-alkyl derivs.,	90194-32-4	5.00 - 10.00 %
New Jersey Right To Know					
	HEAVY PARAF	FI	NIC DISTILLATE	64742-54-7	90.00 - 100.00 %
	Benzenesulfoni sodium salts	сa	acid, C10-60-alkyl derivs.,	90194-32-4	5.00 - 10.00 %
	POLYOLEFIN A	٩M	IIDE ALKENEAMINE	Not Assigned	1.00 - 5.00 %
	LUBRICANT A	DD	ITIVE	Not Assigned	1.00 - 5.00 %

California Prop 65

Proposition 65 warnings are not required for this product

ASHLAND	Page: 9
SAFETY DATA SHEET	Revision Date: 05/22/201
	Print Date: 12/4/2015
	SDS Number: R0171982
All-Climate [™] SAE 20W-50 MOTOR OIL	Version: 1.0
130	

•	based on the results of a risk assessment. Ict are reported in the following inventories: : On TSCA Inventory
DSL	: All components of this product are on the Canadian DSL.
AUSTR	: On the inventory, or in compliance with the inventory
ENCS	: q (quantity restricted)
KECL	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: q (quantity restricted)


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/22/2015



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.H319Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet

ASHLAND	Page: 10
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 12/4/2015
	SDS Number: R0171982
All-Climate [™] SAE 20W-50 MOTOR OIL	Version: 1.0
130	

Ashland internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

 $\label{eq:cercla} \mathsf{CERCLA}: \mathsf{Comprehensive} \ \mathsf{Environmental} \ \mathsf{Response}, \ \mathsf{Compensation}, \ \mathsf{and} \ \mathsf{Liability} \ \mathsf{Act}$

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

ASHLAND	Page: 11
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 12/4/2015
	SDS Number: R0171982
All-Climate™ SAE 20W-50 MOTOR OIL	Version: 1.0
130	

RTK : Right to Know WHMIS : Workplace Hazardous Materials Information System