## **Material Safety Data Sheet**

**TECH RUB-O-MATIC** 



## 1. Product and company identification

Product name : TECH RUB-O-MATIC

Supplier : Same as manufacturer.

Synonym : Not available.

Trade name : RUB-O-MATIC

Material uses : Industrial applications: Cleaning solutions. Rubber chemicals.

Manufacturer : Tech International, 200 E. Coshocton St., Johnstown, Ohio 43031, 1-740-967-9015;

Chemtrec 1-800-424-9300

**Code** : 704, 704G, 704-5G, 704-55G

**MSDS #** : 704, 704-G, 704-5G

 Validation date
 : 2/12/2014.

 Print date
 : 2/12/2014.

In case of emergency : Chemtrec 1-800-424-9300 (24hrs)

CHEMTREC Brazil (Rio De Janeiro): +(55)-2139581449

CHEMTREC Mexico: 01-800-681-9531 CHEMTREC Russia: 8-800-100-6346

Product type : Liquid.

### 2. Hazards identification

### **Emergency overview**

Physical state : Liquid.

Color : Clear. [Light]
Odor : Solvent. [Strong]
Signal word : DANGER!

Hazard statements : EXTREMELY FLAMMABLE LIQUID AND VAPOR. FLAMMABLE. VAPOR MAY

CAUSE FLASH FIRE. CAUSES SKIN IRRITATION. CONTAINS MATERIAL THAT

MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

**Precautionary measures**: Do not breathe vapor or mist. Use only with adequate ventilation. Do not eat, drink or

smoke when using this product. Avoid contact with skin and clothing. Keep away from heat, sparks and flame. Keep container tightly closed. Wash thoroughly after handling.

Routes of entry : Not available.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.Ingestion : No known significant effects or critical hazards.

Skin : Irritating to skin.

**Eyes** : May cause eye irritation.

Potential chronic health effects

**Chronic effects** : Contains material that may cause target organ damage, based on animal data.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Target organs : Contains material which may cause damage to the following organs: cardiovascular

system, central nervous system (CNS).

### 2. Hazards identification

### Over-exposure signs/symptoms

Inhalation : No specific data. : No specific data. Ingestion

Skin : Adverse symptoms may include the following:

> irritation redness

: No specific data. **Eyes** 

**Medical conditions** aggravated by overexposure

: Pre-existing disorders involving any target organs mentioned in this MSDS as being at

risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

## 3. Composition/information on ingredients

Name	CAS number	%
solvent naphtha (petroleum blend), light	64742-89-8	50 - 100

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### 4. First aid measures

: Check for and remove any contact lenses. Immediately flush eyes with plenty of water **Eye contact** 

for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

: In case of contact, immediately flush skin with plenty of water for at least 15 minutes Skin contact

while removing contaminated clothing and shoes. Wash clothing before reuse. Clean

shoes thoroughly before reuse. Get medical attention immediately.

Inhalation : Move exposed person to fresh air. If not breathing, if breathing is irregular or if

respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention

immediately.

Ingestion : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person. Get medical

attention immediately.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

No specific treatment. Treat symptomatically. Contact poison treatment specialist Notes to physician

immediately if large quantities have been ingested or inhaled.

## 5. Fire-fighting measures

Flammability of the product Extremely flammable liquid. In a fire or if heated, a pressure increase will occur and the

container may burst, with the risk of a subsequent explosion. Runoff to sewer may

create fire or explosion hazard.

**Extinguishing media** 

Suitable : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Not suitable : Do not use water jet.

: Promptly isolate the scene by removing all persons from the vicinity of the incident if **Special exposure hazards** there is a fire. No action shall be taken involving any personal risk or without suitable

training. Move containers from fire area if this can be done without risk. Use water

spray to keep fire-exposed containers cool.

## 5. Fire-fighting measures

Hazardous thermal decomposition products

Special protective equipment for fire-fighters

Special remarks on fire hazards

Special remarks on explosion hazards

: No specific data.

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

: Not available.

: Not available.

### 6. Accidental release measures

### **Personal precautions**

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods for cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## 7. Handling and storage

### Handling

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

## 7. Handling and storage

### **Storage**

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8. Exposure controls/personal protection

Occupational exposure limits		TWA (8 hours)		STEL (15 mins)		Ceiling					
Ingredient	List name	ppm	mg/ m³	Other	ppm	mg/ m³	Other	• •	mg/ m³	Other	Notations
solvent naphtha (petroleum blend), light	US ACGIH	400	-	-	-	-	-	-	-	-	

### Consult local authorities for acceptable exposure limits.

## Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### **Engineering measures**

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

# Personal protection Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

#### **Hands**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

### **Eyes**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

## 8. Exposure controls/personal protection

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Other protection
Personal protective
equipment (Pictograms)

Not available.Not available.

## 9. Physical and chemical properties

Physical state : Liquid.

Flash point : Closed cup: -7°C (19.4°F) [Tagliabue.]

Burning time : Not applicable.

Burning rate : Not applicable.

Auto-ignition temperature : 280°C (536°F)

Flammable limits : Lower: 1.3%
Upper: 8%

Color : Clear. [Light]

Color : Clear. [Light]
Odor : Solvent. [Strong]
Taste : Not available.

Molecular weight : Not applicable.

Molecular formula : Not applicable.

pH : Not applicable.

**Boiling/condensation point**: 93.3 to 115.6°C (199.9 to 240.1°F)

Melting/freezing point : <-50°C (<-58°F)
Critical temperature : Not available.

Relative density : 0.73

**Vapor pressure** : 5.3 kPa (40 mm Hg) [room temperature]

Vapor density: Not available.Volatility: 100% (w/w)Odor threshold: Not available.

**Evaporation rate** : >1 (butyl acetate = 1)

SADT : Not available.

Viscosity : Kinematic (room temperature): 0.007 cm²/s (0.7 cSt)

Ionicity (in water): Not available.Dispersibility properties: Not available.Solubility: Not available.Physical/chemical<br/>properties comments: Not available.

## 10. Stability and reactivity

Chemical stability : The

: The product is stable.

**Conditions to avoid** 

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**Incompatible materials** 

: Highly reactive or incompatible with the following materials: oxidizing materials

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 10. Stability and reactivity

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

## 11. Toxicological information

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
solvent naphtha (petroleum blend), light	LC50 Inhalation Gas.	Rat	3400 ppm	4 hours
	LD50 Dermal LD50 Oral	Rat Rat	>4000 mg/kg >8000 mg/kg	-

**Conclusion/Summary** 

: Not available.

**Chronic toxicity** 

Not available.

**Conclusion/Summary** 

: Not available.

Irritation/Corrosion

Not available.

**Conclusion/Summary** 

: Not available.

**Sensitizer** 

Not available.

Conclusion/Summary

: Not available.

Carcinogenicity

Not available.

**Conclusion/Summary** 

: Not available.

**Classification** 

Not available.

**Mutagenicity** 

Not available.

**Conclusion/Summary** 

: Not available.

**Teratogenicity** 

Not available.

**Conclusion/Summary** 

: Not available.

Reproductive toxicity

Not available.

Conclusion/Summary : Not available.

Synergistic products : Not available.

## 12. Ecological information

**Ecotoxicity** 

: No known significant effects or critical hazards.

Aquatic ecotoxicity

Not available.

**Conclusion/Summary**: Not available.

Persistence/degradability

**2/12/2014.** 704, 704-G, 704-5G **6/9** 

## 12. Ecological information

Not available.

**Conclusion/Summary** Partition coefficient: n-

: Not available. : Not available.

octanol/water **Bioconcentration factor** 

: Not available.

**Mobility** Toxicity of the products of

biodegradation

: Not available. : Not available.

Other adverse effects

: No known significant effects or critical hazards.

## 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Waste stream : Not available. **RCRA** classification : Not available.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 4. Transport information

LE 3 N.O.S.	II	_	
blend),		AAMMAT LIGHT	
LE 3 N.O.S. phtha blend),	II		
LE 3 N.O.S. phtha blend),	II		
1	N.O.S. phtha	N.O.S. phtha	N.O.S. phtha

14. Transport information							
IMDG Class	1993	FLAMMABLE LIQUIDS, N.O.S. (solvent naphtha (petroleum blend), light)	3	II	3	-	
IATA-DGR Class	1993	FLAMMABLE LIQUIDS, N.O.S. (solvent naphtha (petroleum blend), light)	3	II	3	-	

PG\*: Packing group

## 15. Regulatory information

United States inventory (TSCA 8b)

y

: All components are listed or exempted.

WHMIS (Canada)

: Class B-2: Flammable liquid

Class D-1B: Material causing immediate and serious toxic effects (Toxic).

**Canadian lists** 

**Canadian NPRI** : The following components are listed: Solvent naphtha light aliphatic

CEPA Toxic substances : None of the components are listed.

Canada inventory : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

### International regulations

International lists : Australia inventory (AICS): All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Japan inventory: Not determined.

**Korea inventory**: All components are listed or exempted. **Malaysia Inventory (EHS Register)**: Not determined.

**New Zealand Inventory of Chemicals (NZIoC)**: All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted.

Taiwan inventory (CSNN): Not determined.

Convention List School

Convention List Schedule

: Not listed

I Chemicals

**Chemical Weapons Convention List Schedule** 

: Not listed

Il Chemicals

Chemical Weapons
Convention List Schedule

: Not listed


III Chemicals

### 16. Other information

Label requirements

: EXTREMELY FLAMMABLE LIQUID AND VAPOR. FLAMMABLE. VAPOR MAY CAUSE FLASH FIRE. CAUSES SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

References : Not available.

Other special : Not available.

considerations

Date of printing: 2/12/2014.Date of issue: 2/12/2014.Date of previous issue: 2/3/2014.Version: 0.04

Prepared by : Not available.

▼ Indicates information that has changed from previously issued version.

### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.