

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 235
Product name STRIP-IT BASEBOARD STRIPPER
Effective date 13-Jun-2007
Manufacturer information CSI PRODUCTS, INC.
ADDISON, IL 60101 United States
Manufacturer phone General Assistance 1-630-543-7600
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646

2. Hazards Identification

Emergency overview CONTENTS UNDER PRESSURE.
Aerosol. Pressurized container may explode when exposed to heat or flame.

Corrosive. Causes skin and eye burns. Irritating to respiratory system. May be harmful if absorbed through skin. Prolonged exposure may cause chronic effects.

OSHA regulatory status This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

Potential health effects

Routes of exposure Eye contact. Skin contact. Inhalation.

Eyes This product causes eye burns. Risk of serious damage to eyes.

Skin Causes skin burns. Harmful in contact with skin.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Causes burns. Irritating to respiratory system. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract. May cause delayed lung damage.

Target organs Kidney.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged and may cause blood damage. These effects have not been observed in humans.

Chronic effects Blood. Central nervous system. Liver. Respiratory system.
Unconsciousness. Liver injury may occur. Kidney injury may occur. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage.

Signs and symptoms Discomfort in the chest. Narcosis. Cyanosis. Liver enlargement. Jaundice.

3. Composition / Information on Ingredients

Components	CAS #	Percent
2-Butoxyethanol	111-76-2	10 - 15
Monethanolamine	141-43-5	5 - 8
n-Butane	106-97-8	3 - 5
Propane	74-98-6	3 - 5
Non-hazardous and other components below reportable levels		60 - 80

Material name: Baseboard Stripper
Material ID: 917 Revision date: 13-JUN-2007 Print date: 13-JUN-2007

MSDS US
1 / 6

4. First Aid Measures

First aid procedures

Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately.
Skin contact	Immediately flush skin with plenty of water. Remove and isolate contaminated clothing and shoes. Get medical attention immediately. For minor skin contact, avoid spreading material on unaffected skin. Wash clothing separately before reuse.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention immediately.
Ingestion	Have victim rinse mouth thoroughly with water. Get medical attention immediately. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Notes to physician

In case of shortness of breath, give oxygen. Keep victim warm. Symptoms may be delayed.

General advice

Immediate medical attention is required. In case of shortness of breath, give oxygen. Keep victim warm.

5. Fire Fighting Measures

Flammable properties

Containers may explode when heated. Vapor or gas may spread to distant ignition sources and flash back.

Extinguishing media

Suitable extinguishing media Alcohol foam. Dry chemical. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Protection of firefighters

Specific hazards arising from the chemical Fire may produce irritating, corrosive and/or toxic gases.

Protective equipment and precautions for firefighters In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

Specific hazards

Fire may produce irritating, corrosive and/or toxic gases.

6. Accidental Release Measures

Personal precautions

Ensure adequate ventilation. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Keep unnecessary personnel away.

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.

Methods for cleaning up

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Do not breathe gas/fumes/vapor/spray. Do not get this material on clothing. Avoid prolonged exposure.

Storage

Level 1 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat, sparks, and flame. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Use care in handling/storage.

8. Exposure Controls / Personal Protection

Exposure limits**ACGIH**

Components	CAS #	TWA	STEL	Ceiling
2-Butoxyethanol	111-76-2	20 ppm	Not established	Not established
Monethanolamine	141-43-5	3 ppm	6 ppm	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
2-Butoxyethanol	111-76-2	50 ppm	Not established	Not established
Monethanolamine	141-43-5	3 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment**Eye / face protection**

Wear chemical goggles.

Skin protection

Do not get this material on clothing. Wear appropriate chemical resistant gloves. Structural firefighters protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations. Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent). Wear chemical protective equipment that is specifically recommended by the manufacturer.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General hygiene considerations

Do not get this material in contact with skin. Do not get this material on clothing. Avoid contact with eyes. Avoid contact with clothing. When using do not eat or drink. Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Color	Cloudy.
Odor	Not established.
Physical state	Liquid.
Form	Aerosol.
Flammability (HOC)	6.8491 kJ/g estimated
Flash back	No
Pressure	45 - 55 psig @ 70 F
Solubility	Partially
Flash point	-156 °F (-104.4 °C) estimated
Boiling point	222.8 °F (106.1 °C) estimated
Specific gravity	0.952 estimated
pH	11.4 - 12.4

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition. Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.

Hazardous decomposition products

Irritants. Toxic gas. May include oxides of nitrogen.

11. Toxicological Information

Acute effects

Acute LD50: 3290 mg/kg estimated, Rat, Oral
Acute LD50: 1928 mg/kg estimated, Rat, Dermal
Acute LC50: 17 mg/l/4h estimated, Rat, Inhalation
Causes burns.

Local effects

Liver toxicity. Blood disorder may occur after ingestion. Irritating to respiratory system.

Chronic effects

Hazardous by OSHA criteria. This product may be harmful if it is absorbed through the skin. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged or repeated exposure may cause lung injury. Prolonged exposure may cause chronic effects.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

Subchronic effects

Kidney injury may occur. Blood disorder may occur after prolonged inhalation. Blood disorder may occur after prolonged skin contact.

Neurological effects

Hazardous by OSHA criteria.

Mutagenicity

Not expected to be hazardous by OSHA criteria.

Reproductive effects

Not expected to be hazardous by OSHA criteria.

Teratogenicity

Not expected to be hazardous by OSHA criteria.

Further information

Symptoms may be delayed.

12. Ecological Information

Ecotoxicity

LC50 1504 mg/L estimated, Fish, 96.00 Hours,
EC50 965 mg/L estimated, Daphnia, 48.00 Hours,
IC50 225 mg/L estimated, Algae, 72.00 Hours,
Components of this product have been identified as having potential environmental concerns.

13. Disposal Considerations

Waste codes

D001: Waste Flammable material with a flash point <140 F

Disposal instructions

Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D

Subsidiary hazard class None

Additional information:

Packaging exceptions 156, 306

Packaging non bulk 156, 306

Packaging bulk None

IMDG**Basic shipping requirements:**

Proper shipping name AEROSOLS, flammable, corrosive
Hazard class 2.1
UN number 1950

Additional information:

Item 5FC
Labels required 2.1
+8

Transport Category 1

**IATA****Basic shipping requirements:**

Proper shipping name Aerosols, flammable, containing substances in Class 8, Packing Group III
Hazard class 2.1
Subsidiary hazard class 8
UN number 1950



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

Chemical Name	Inventory ID	Status
2-Butoxyethanol	111-76-2	Present
Monethanolamine	141-43-5	Present
n-Butane	106-97-8	Present
Propane	74-98-6	Present

16. Other Information

HMIS® ratings

Health: 3*
Flammability: 2
Physical hazard: 0

Prepared by

Regulatory Compliance

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Issue date

13-Jun-2007