

[Close this window](#)

MSDS

**Common Name:** ALL-STATE PHOS-COPPER BRAZING ALLOYS

**Manufacturer:** ESAB

**MSDS Revision Date:** 3/2/2006

**MSDS Format:** No Format Specified

**Grainger Item Number(s):** 2C177, 2C201, 2C209

**Manufacturer Model Number(s):** 69050005, 69050055, 69060062, 69060072

## MSDS Table of Contents

Click the desired link below to jump directly to that section in the MSDS.

[I. PRODUCT IDENTIFICATION](#)

[II. HAZARDOUS INGREDIENTS](#)

[III. PHYSICAL DATA](#)

[IV. FIRE & EXPLOSION HAZARD](#)

[V. REACTIVITY DATA](#)

[VI. PHYSICAL AND HEALTH HAZARD DATA](#)

[VII. PRECAUTIONS FOR SAFE HANDLING AND USE/APPLICABLE](#)

## MATERIAL SAFETY DATA SHEET

(ESSENTIALLY SIMILAR TO U.S. DEPARTMENT OF LABOR SUGGESTED FORM FOR HAZARD COMMUNICATION COMPLIANCE)

FORM NO. MSDS #: 17-C

### NFPA RATINGS:

HEALTH 1  
FIRE 0  
REACTIVITY 0  
SPECIAL

### HAZARD RATINGS:

4 = EXTREME  
3 = HIGH  
2 = MODERATE  
1 = SLIGHT  
0 = INSIGNIFICANT

DATE REVISED: 03/02/2006

## I. PRODUCT IDENTIFICATION



**PRODUCT TYPE:** ALL-STATE PHOS-COPPER BRAZING ALLOYS

**MANUFACTURER:** THE ESAB GROUP, INC.

**ADDRESS:**  
801 WILSON AVENUE

HANOVER, PA 17331

WEBSITE: WWW.ESABNA.COM

TELEPHONE NO.:  
1-717-637-8911  
1-800-933-7070

EMERGENCY NO.: 1-717-637-8911  
(CHEMTREC): 1-800-424-9300

**PRODUCT DESCRIPTION:**

THESE PHOS-COPPER ALLOYS ARE BARE RODS CUT OR CAST IN STANDARD LENGTHS INTENDED TO BE USED FOR BRAZING OF CERTAIN BASE MATERIALS.

**NOMINAL COMPOSITION (%)**

PRODUCT TRADE NAME	COPPER	PHOSPHOROUS	SILVER
ALL-STATE SILFLO(R*) "0" (1)	90 - 95	5 - 10	
ALL-STATE SILFLO(R*) "5" (1)	85 - 95	1 - 10	1 - 10
ALL-STATE SILFLO(R*) "15" (1)	75 - 85	1 - 10	10 - 20
ALL-STATE NO. 21 (1)	85 - 95	1 - 10	
ALL-STATE NO. 23 (1)	85 - 95	1 - 10	1 - 5

(1) SEE NOTE IN SECTION VI

THE ESAB GROUP REQUESTS THE USERS OF THESE PRODUCTS TO STUDY THIS MATERIAL SAFETY DATA SHEET (MSDS) AND THE PRODUCT LABELS AND BECOME FULLY AWARE OF THE PRODUCT HAZARDS AND SAFETY INFORMATION. TO PROMOTE THE SAFE USE OF THESE PRODUCTS A USER SHOULD (1) NOTIFY AND TRAIN ITS EMPLOYEES, AGENTS AND CONTRACTORS CONCERNING THE INFORMATION ON THIS MSDS AND ANY PRODUCT HAZARDS AND SAFETY INFORMATION, (2) FURNISH THIS SAME INFORMATION TO EACH OF ITS CUSTOMERS FOR THESE PRODUCTS, AND (3) REQUEST THAT SUCH CUSTOMERS NOTIFY AND TRAIN THEIR EMPLOYEES AND CUSTOMERS, FOR THESE PRODUCTS, OF THE SAME PRODUCT HAZARDS AND SAFETY INFORMATION.

## II. HAZARDOUS INGREDIENTS



**IMPORTANT:**

THIS SECTION COVERS THE MATERIALS FROM WHICH THIS PRODUCT IS MANUFACTURED. THE FUMES AND GASES PRODUCED DURING NORMAL USE OF THESE PRODUCTS ARE COVERED IN SECTION V. THE TERM HAZARDOUS SHOULD BE INTERPRETED AS A TERM REQUIRED AND DEFINED BY LAWS, STATUTES, OR REGULATIONS, AND DOES NOT NECESSARILY IMPLY THE EXISTENCE OF ANY HAZARD WHEN THE PRODUCTS ARE USED AS DIRECTED BY THE ESAB GROUP.

MATERIAL	(CAS NO.)	SARA	ACGIH TLV		OSHA - PEL	
			TWA (MG/M3)		TWA (MG/M3)	STEL (MG/M3)
COPPER	(7440-50-8)	*	0.2 (FUME)		0.1 (FUME)	
PHOSPHOROUS (YELLOW)	(7723-14-0)	*	0.1		0.1	
SILVER	(7440-22-4)	*	0.1 (METAL) 0.01 (SOLUBLE CMPDS.)		0.01 (METAL) 0.01 (SOLUBLE CMPDS.)	

**NOTE:**

IN THE INGREDIENTS TABLE, AN ASTERISK (\*) AFTER THE CAS NUMBER INDICATES A

TOXIC CHEMICAL SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 (SARA) AND 40 CFR PART 372.

SOME OF THESE PRODUCTS MAY NOT CONTAIN ALL OF THE MATERIALS LISTED. FOR DETAILS OF COMPOSITION, REFER TO THE COMPOSITION TABLE IN SECTION I.

### III. PHYSICAL DATA



AS SHIPPED, THESE PRODUCTS ARE NONFLAMMABLE, NON-EXPLOSIVE, NON-REACTIVE, AND NON-HAZARDOUS

#### PHYSICAL STATE:

GAS ( )

LIQUID ( )

SOLID (X)

ODOR AND APPEARANCE: COPPER COLORED BARE WIRE. ODORLESS.

### IV. FIRE & EXPLOSION HAZARD



#### FLAMMABLE/EXPLOSIVE:

NO (X)

YES ( )

UNDER WHAT CONDITIONS: ONLY THE PACKAGING FOR THIS PRODUCT WILL BURN.

#### EXTINGUISHING MEDIA:

THIS PRODUCT WILL NOT BURN; HOWEVER, WELDING ARCS AND SPARKS CAN IGNITE COMBUSTIBLE AND FLAMMABLE MATERIALS. USE THE EXTINGUISHING MEDIA RECOMMENDED FOR THE BURNING MATERIALS AND FIRE SITUATION. SEE ANSI Z49.1 "SAFETY IN WELDING AND CUTTING" AND "SAFE PRACTICES" CODE: SP, PUBLISHED BY THE AMERICAN WELDING SOCIETY, P. O. BOX 351040, MIAMI, FL 33135, AND NFPA 51B "CUTTING AND WELDING PROCESSES," PUBLISHED BY THE NATIONAL FIRE PROTECTION ASSOCIATION, BATTERYMARCH PARK, QUINCY, MA 02269 FOR ADDITIONAL FIRE PREVENTION AND PROTECTION INFORMATION.

### V. REACTIVITY DATA



#### STABILITY:

STABLE (X)

UNSTABLE ( )

POLYMERIZATION WILL NOT OCCUR

INCOMPATIBLE PRODUCTS: NONE CURRENTLY KNOWN

#### HAZARDOUS DECOMPOSITION PRODUCTS:

BRAZING FUMES AND GASES CANNOT BE CLASSIFIED SIMPLY. THE COMPOSITION AND QUANTITY OF BOTH ARE DEPENDENT UPON THE MATERIAL BEING WORKED, THE PROCESS, PROCEDURES, AND CONSUMABLES USED. OTHER CONDITIONS WHICH ALSO INFLUENCE THE COMPOSITION AND QUANTITY OF THE FUMES AND GASES TO WHICH WORKERS MAY BE EXPOSED INCLUDE: COATINGS ON THE MATERIAL BEING WORKED (SUCH AS PAINT, PLATING OR GALVANIZING), THE NUMBER OF WELDING OPERATIONS AND THE VOLUME OF THE WORK AREA, THE QUALITY AND AMOUNT OF VENTILATION, THE POSITION OF THE WORKER'S HEAD WITH RESPECT TO THE FUME PLUME, AS WELL AS THE PRESENCE OF CONTAMINANTS IN THE ATMOSPHERE (SUCH AS CHLORINATED HYDROCARBON VAPORS FROM CLEANING OR PAINTING ACTIVITIES). WHEN THE MATERIALS ARE CONSUMED, THE FUME AND GAS DECOMPOSITION PRODUCTS GENERATED ARE DIFFERENT IN PERCENT AND FORM FROM THE INGREDIENTS LISTED IN SECTION II. DECOMPOSITION PRODUCTS OF NORMAL

OPERATION INCLUDE THOSE ORIGINATING FROM THE VOLATILIZATION, REACTION, OR OXIDATION OF THE INGREDIENTS, PLUS THOSE FROM THE MATERIAL BEING WORKED AND THE COATINGS ETC. NOTED ABOVE.

REASONABLY EXPECTED DECOMPOSITION PRODUCTS FROM NORMAL USE OF THESE PRODUCTS INCLUDE A COMPLEX OF THE OXIDES OF THE MATERIALS LISTED IN SECTION II, AS WELL AS CARBON MONOXIDE, CARBON DIOXIDE, OZONE AND NITROGEN OXIDES (REFER TO "CHARACTERIZATION OF ARC WELDING FUME" AVAILABLE FROM THE AMERICAN WELDING SOCIETY). THE FUME LIMIT FOR COPPER MAY BE REACHED BEFORE THE GENERAL LIMIT FOR WELDING FUMES OF 5 MG/M3 IS REACHED. MONITOR FUMES FOR COPPER LEVELS. THE ONLY WAY TO DETERMINE THE TRUE IDENTITY OF THE DECOMPOSITION PRODUCTS IS BY SAMPLING AND ANALYSIS. THE COMPOSITION AND QUANTITY OF THE FUMES AND GASES TO WHICH A WORKER MAY BE OVEREXPOSED CAN BE DETERMINED FROM A SAMPLE OBTAINED FROM INSIDE THE WELDER'S HELMET, IF WORN, OR IN THE WORKERS BREATHING ZONE. SEE ANSI/AWS F1.1 "METHOD FOR SAMPLING AIRBORNE PARTICLES GENERATED BY WELDING AND ALLIED PROCESSES," AVAILABLE FROM THE AMERICAN WELDING SOCIETY.

## VI. PHYSICAL AND HEALTH HAZARD DATA



ELECTRIC ARC WORKING MAY CREATE ONE OR MORE OF THE FOLLOWING HEALTH OR PHYSICAL HAZARDS. FUMES AND GASES CAN BE DANGEROUS TO YOUR HEALTH. ELECTRIC SHOCK CAN KILL YOU. ARC RAYS CAN INJURE EYES AND BURN SKIN. NOISE CAN DAMAGE HEARING. BRAZING ALLOYS ARE FREQUENTLY USED WITH A FLUORIDE-TYPE FLUX. IF APPLICABLE, FLUX FUME SHOULD BE CONSIDERED IN EVALUATION OF HAZARDS.

### ROUTE OF OVEREXPOSURE:

THE PRIMARY ROUTE OF ENTRY OF THE DECOMPOSITION PRODUCTS IS BY INHALATION. SKIN CONTACT, EYE CONTACT, AND INGESTION ARE POSSIBLE. ABSORPTION BY SKIN CONTACT IS UNLIKELY. WHEN THESE PRODUCTS ARE USED AS RECOMMENDED BY THE ESAB GROUP, AND VENTILATION MAINTAINS EXPOSURE TO THE DECOMPOSITION PRODUCTS BELOW THE LIMITS RECOMMENDED IN THIS SECTION, OVEREXPOSURE IS UNLIKELY.

EFFECTS OF ACUTE (SHORT-TERM) OVEREXPOSURE TO THE GASES, FUMES, AND DUSTS MAY INCLUDE IRRITATION OF THE EYES, LUNGS, NOSE, AND THROAT. SOME TOXIC GASES ASSOCIATED WITH WELDING MAY CAUSE PULMONARY EDEMA, ASPHYXIATION, AND DEATH. ACUTE OVEREXPOSURE MAY INCLUDE SIGNS AND SYMPTOMS SUCH AS WATERY EYES, NOSE AND THROAT IRRITATION, HEADACHE, DIZZINESS, DIFFICULTY IN BREATHING, FREQUENT COUGHING, OR CHEST PAIN. THE PRESENCE OF COPPER IN FUME CAN CAUSE METAL FUME FEVER. SHORT TERM SYMPTOMS MAY INCLUDE A METALLIC TASTE IN THE MOUTH, DRYNESS OR IRRITATION OF THE THROAT FOLLOWED BY COUGHING, SHORTNESS OF BREATH, NAUSEA, FEVER, BODY ACHE, AND CHILLS. SYMPTOMS USUALLY DISAPPEAR WITHIN 24 HOURS.

### PRE-EXISTING MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

INDIVIDUALS WITH ALLERGIES OR IMPAIRED RESPIRATORY FUNCTION MAY HAVE SYMPTOMS WORSENED BY EXPOSURE TO WELDING FUMES; HOWEVER, SUCH REACTION CANNOT BE PREDICTED DUE TO THE VARIATION IN COMPOSITION AND QUANTITY OF THE DECOMPOSITION PRODUCTS.

EFFECTS OF CHRONIC (LONG-TERM) OVEREXPOSURE TO AIR CONTAMINANTS MAY LEAD TO THEIR ACCUMULATION IN THE LUNGS, A CONDITION WHICH MAY BE SEEN AS DENSE AREAS ON CHEST X-RAYS. THE SEVERITY OF THE CHANGE IS PROPORTIONAL TO THE LENGTH OF THE EXPOSURE. THE CHANGES SEEN ARE NOT NECESSARILY ASSOCIATED WITH SYMPTOMS OR SIGNS OF REDUCED LUNG FUNCTION OR DISEASE. IN ADDITION, THE CHANGES ON X-RAYS MAY BE CAUSED BY NON-WORK FACTORS SUCH AS SMOKING, ETC. COPPER POISONING HAS BEEN REPORTED IN THE LITERATURE FROM EXPOSURE TO HIGH LEVELS OF COPPER. LIVER DAMAGE CAN OCCUR DUE TO COPPER ACCUMULATION IN THE LIVER; THE DAMAGE IS CHARACTERIZED BY CELL DESTRUCTION AND CIRRHOSIS. HIGH LEVELS OF COPPER MAY CAUSE CENTRAL NERVOUS SYSTEM DAMAGE CHARACTERIZED BY NERVE FIBER SEPARATION AND CEREBRAL DEGENERATION. OVEREXPOSURE TO PHOSPHORUS MAY CAUSE NECROSIS OF THE MANDIBLE, TERMED "PHOSSY JAW". OVEREXPOSURE TO SILVER MAY RESULT IN ARGYRIA, A PERMANENT PIGMENTATION

(GRAY TO PURPLE) OF THE SKIN AND EYES. EXPOSURE TO HIGH SILVER LEVELS HAS RESULTED IN RESPIRATORY PROBLEMS AND STOMACH PAINS.

EXPOSURE LIMITS FOR THE INGREDIENTS ARE LISTED IN SECTION II. THE ACGIH AND THE 1989 OSHA TWA FOR WELDING FUME IS 5 MG/M3. AT TIMES THE LIMIT FOR A PARTICULAR HAZARDOUS CHEMICAL IS REACHED BEFORE THE LIMIT FOR WELDING FUMES. TLV-TWAS SHOULD BE USED AS A GUIDE IN THE CONTROL OF HEALTH HAZARDS AND NOT AS FINE LINES BETWEEN SAFE AND EXCESSIVE CONCENTRATIONS. AS NOTED IN SECTION V, THE BRAZING FUME IS A MIXTURE OF MANY COMPONENTS. THEREFORE, A STATUTORY COMPUTATION OF THE EQUIVALENT EXPOSURE IS REQUIRED. THE EQUIVALENT EXPOSURE VALUE FOR THE BRAZING FUME MIXTURE SHALL ALWAYS BE LESS THAN ONE. WHEN THESE PRODUCTS ARE USED AS RECOMMENDED BY THE ESAB GROUP, AND THE PREVENTIVE MEASURES TAUGHT IN THIS MSDS ARE FOLLOWED, OVEREXPOSURE TO HAZARDOUS SUBSTANCES WILL NOT OCCUR.

**EMERGENCY FIRST AID MEASURES:**

IN CASE OF EMERGENCY, CALL FOR MEDICAL AID. EMPLOY FIRST AID TECHNIQUE RECOMMENDED BY THE RED CROSS. IF BREATHING IS DIFFICULT, GIVE OXYGEN AND CALL FOR A PHYSICIAN. FOR ELECTRIC SHOCK, DISCONNECT AND TURN OFF THE POWER. IF NOT BREATHING, BEGIN ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH. IF NO DETECTABLE PULSE, BEGIN CARDIO PULMONARY RESUSCITATION (CPR). IMMEDIATELY CALL A PHYSICIAN. FOR ARC BURN, APPLY COLD, CLEAN COMPRESSES AND CALL A PHYSICIAN.

CARCINOGENIC ASSESSMENT (NTP ANNUAL REPORT, IARC MONOGRAPHS, OTHER): NONE

**(1) WARNING:**

THIS PRODUCT, WHEN USED FOR WELDING OR CUTTING, PRODUCES FUMES OR GASES WHICH CONTAIN CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS AND, IN SOME CASES, CANCER. (CALIFORNIA HEALTH & SAFETY CODE SUBSECTION 25249.5 ET SEQ.)

## **VII. PRECAUTIONS FOR SAFE HANDLING AND USE/APPLICABLE**



### **CONTROL MEASURES**

READ AND UNDERSTAND THE MANUFACTURER'S INSTRUCTIONS AND THE PRECAUTIONARY LABEL ON THIS PRODUCT. SEE AMERICAN NATIONAL STANDARD Z-49.1, "SAFETY IN WELDING AND CUTTING," PUBLISHED BY THE AMERICAN WELDING SOCIETY, P. O. BOX 351040, MIAMI, FL 33135 AND OSHA PUBLICATION 2206 (29 C.F.R. 1910), U.S. GOVERNMENT PRINTING OFFICE, SUPERINTENDENT OF DOCUMENTS, P.O. BOX 371954, PITTSBURGH, PA 15250-7954 FOR MORE DETAIL ON MANY OF THE FOLLOWING:

**VENTILATION:**

USE ENOUGH VENTILATION, LOCAL EXHAUST AT THE ARC, OR BOTH, TO KEEP THE EXPOSURE WITHIN LEGAL LIMITS. IN THE WORKER'S BREATHING ZONE AND THE GENERAL AREA, FUMES AND GASES MUST BE KEPT BELOW THE TLVS AND THE EQUIVALENT EXPOSURE MUST COMPUTE TO LESS THAN ONE. TRAIN THE WELDER TO KEEP HIS HEAD OUT OF THE FUMES.

**RESPIRATORY PROTECTION:**

USE RESPIRABLE FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN WELDING IN CONFINED SPACE OR WHERE LOCAL EXHAUST OR VENTILATION DOES NOT KEEP EXPOSURE BELOW TLVS.

**EYE PROTECTION:**

WEAR HELMET OR USE FACE SHIELD WITH FILTER LENS. AS A RULE OF THUMB, START WITH A SHADE WHICH IS TOO DARK TO SEE THE WELD ZONE. THEN GO TO THE NEXT LIGHTER SHADE WHICH GIVES SUFFICIENT VIEW OF THE WELD ZONE. PROVIDE PROTECTIVE SCREENS AND FLASH GOGGLES, IF NECESSARY, TO SHIELD OTHERS.

**PROTECTIVE CLOTHING:**

WEAR HEAD, HAND, AND BODY PROTECTION WHICH HELP TO PREVENT INJURY FROM RADIATION, SPARKS AND ELECTRICAL SHOCK. SEE ANSI Z-49.1. AT A MINIMUM, THIS INCLUDES WELDER'S GLOVES AND A PROTECTIVE FACE SHIELD AND MAY INCLUDE ARM PROTECTORS, APRONS, HATS, SHOULDER PROTECTION, AS WELL AS DARK SUBSTANTIAL

CLOTHING. TRAIN THE WELDER NOT TO TOUCH LIVE ELECTRICAL PARTS AND TO INSULATE HIMSELF FROM WORK AND GROUND.

PROCEDURE FOR CLEANUP OF SPILLS OR LEAKS: NOT APPLICABLE

WASTE DISPOSAL METHOD:

PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE CONTAINER, OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

THE OPINIONS EXPRESSED IN THIS MSDS ARE THOSE OF QUALIFIED EXPERTS WITHIN THE ESAB GROUP. WE BELIEVE THAT THE INFORMATION CONTAINED HEREIN IS CURRENT AS OF THE DATE OF THIS MSDS. SINCE THE USE OF THIS INFORMATION AND THESE OPINIONS AND THE CONDITIONS OF USE OF THESE PRODUCTS ARE NOT WITHIN THE CONTROL OF THE ESAB GROUP, IT IS THE USER'S OBLIGATION TO DETERMINE THE CONDITIONS OF SAFE USE OF THESE PRODUCTS.

PRODUCT IDENTITY: ALL-STATE PHOS-COPPER BRAZING ALLOYS