

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List)

Acoustical Ceiling Tile Restorer/White

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name ProCoat Products, Inc.	Emergency Telephone Number (781) 767-2270
Address (Number, Street, City, State, and ZIP Code) 260 Centre Street, Suite D Holbrook, Massachusetts 02343	Telephone Number for Information (781) 767-2270
U.S.A.	Date Prepared June 26, 2007
	Signature of Preparer (optional)

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	VOC % (optional)
Acetone	67-64-1	1000 ppm	750 ppm	N/A
Isoparaffinic Hydrocarbon	64742-47-8	400 ppm	400 ppm	
Isopropyl Alcohol	67-63-0	400 ppm	400 ppm	N/A
Propane/N-Butane	68476-86-8	1000 ppm	600 ppm	N/A
Titanium Dioxide	13463677	5MG/M3	10MG/M3	N/A
Heptane	142-82-5	400 ppm	400 ppm	N/A

Status. All ingredients are listed. CERCLA RO – 40 CFR 302.4: Not applicable

Section III – Physical/Chemical Characteristics

Boiling Point	Not Est.	Specific Gravity ($H_2O = 1$) @ 25 C.	0.93
Vapor Pressure (mm Hg.) n/a	N/D	Melting Point	N/A
Vapor Density (AIR = 1)	>1	Evaporation Rate (Butyl Acetate = 1)	>1

Solubility in Water

0%

Appearance and Odor

White Spray- Solvent Odor

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) : <100F TCC: Not Established	Flammable Limits	LEL	UEL
Flame Protection: More than 18"	% by volume	Not Est.	Not Est.
Extinguishing Media Co2, Standard Foam, Dry Chemical, Halon			
Special Fire Fighting Procedures Wear self-contained breathing apparatus.			

Unusual Fire and Explosion Hazards Hazardous Products of Combustion: May form carbondioxide, carbon monoxide, phosgene, hydrogen chloride, chlorine. Exposure to temperature above 120 degrees F may cause bursting.
 Autoignition Temperature: Not Established

(Reproduce locally) NFPA Rating: Health 2 Flammability 3 Reactivity 0 OSHA 174, Sept. 1985
 HMIS Rating: Health 2 Flammability 3 Reactivity 0

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid temperatures above 120F
	Stable	X	
Incompatibility (Materials to Avoid)		May effect certain plastics. Store away from heat and open flame	
Hazardous Decomposition or Byproducts		Carbon Monoxide, Carbon Dioxide from heating	
Hazardous Polymerization	May Occur		Conditions to Avoid N/A
	Will Not Occur	X	

Section VI – Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?	Eyes?
	Yes	Yes	Yes	Yes

Health Hazards (Acute and Chronic)
Target Organs: Heart, Liver, Skin, Eyes and Central Nervous System.
 Primary Route(s) of entry: Ingestion, Inhalation, Skin Contact, Eye Contact.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
ACGIH: Possible	No	No	No

Potential Health Effects: None expected.
 Signs and Symptoms of Exposure May cause pain, irritation, redness, slight corneal injury.
 Skin: May cause drying or flaking, irritation, burning sensation, swallowing: May cause gastrointestinal disturbances, nausea, vomiting, diarrhea. Inhalation: Over exposure may cause nausea, dizziness, headache and upper respiratory discomfort, irregular heart beat.
 Medical Conditions Skin sensitivity, chemical allergies, heart condition.
 Generally Aggravated by ExpoSURE

Emergency and First Aid Procedures Eyes: Flush with water for 15 min. If irritation persists, seek medical attention. Skin: Wash with soap and water. If irritation persists, seek medical attention.
 Swallowing: *Do not induce vomiting in order to avoid aspiration into lungs. Seek medical attention immediately.
 Inhalation: Remove to fresh air. *If lavage is performed, suggest endotracheal and/or esophageal control. Do not administer sympathomimetic drugs unless absolutely necessary.

Section VII – Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled
 Small Spill: Absorb liquid on vermiculite, floor absorbent or other absorbent material. Use in well ventilated areas.
 Large Spill: Evacuate area. Remove all sources of ignition. Contain liquid. Prevent run-off to sewer.

Waste Disposal Method
 Dispose of spilled material in accordance with all applicable local, state and federal regulations.

Precautions to be Taken in Handling and Storage Do not store where temperatures exceed 120 degrees F. Keep out of reach of children. Wash hands before eating or smoking after using.

Other Precautions
 Transport: DOT Information –49 CFR 172.101. DOT Description: Consumer Commodity DOT Hazard Class: ORM-D
 Container/Mode: 16oz. Aerosol Can UN ID Number: 1950

Section VIII – Control Measures

Respiratory Protection (Specify Type)
 Not required.

Ventilation	Local Exhaust Recommended	Special None
	Mechanical (General) General ventilation recommended to control the level of vapors.	Other Respiratory Protection: Not required

Protective Gloves For short usage none required Safety goggles.	Eye Protection For short usage none required	Other
--	---	-------

Other Protective Clothing or Equipment
 None.

Work/Hygienic Practices