

# Franklin International

## MATERIAL SAFETY DATA SHEET

MSDS Name: Ace Multipurpose Floor Covering Adhesive  
MSDS Number: 601135

Revision Date: 061404  
Page Number: 1 of 4

---

### SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Ace Multipurpose Floor Covering Adhesive  
CAS Number: none  
HMIS Hazard Rating: Health: 1 Fire: 1 Reactivity: 0

Company Identification: Franklin International  
2020 Bruck Street  
Columbus OH 43207

Contact: Franklin Technical Services  
Telephone/Fax: (800) 877-4583 (614) 445-1493  
Emergency Phone (24 Hour): Franklin Security  
(614) 445-1300  
Chemtec (24 Hour): (800) 424-9300  
Chemtec International: (703) 527-3887

Product Class: Polymer emulsion  
Product Use: adhesive  
Product Code: 7400

Division: Construction Adhesives & Sealants

### SECTION 2 - COMPOSITION AND INFORMATION ON INGREDIENTS

Hazardous Ingredients CAS Number Percent  
Product contains no hazardous ingredients or they are below reportable levels.

OSHA PELs & ACGIH TLVs are listed in Section 8 where applicable.

### SECTION 3 - HAZARD IDENTIFICATION

#### EMERGENCY OVERVIEW:

Beige, light bodied mastic. Mild odor. Extremely sticky in the wet state.

#### ROUTES OF ENTRY:

Ingestion: Yes  
Inhalation: Yes  
Skin: Yes  
Eye: Yes

#### INHALATION:

May be irritating to upper respiratory tract.

#### INGESTION:

Ingestion is not a probable route of exposure. Harmful if swallowed.

#### SKIN:

Prolonged or repeated skin contact can cause irritation.

#### EYE:

Mildly irritating to eyes.

#### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Under conditions of normal use chronic affects are not expected.

Possible aggravation of pre-existing skin conditions.

#### CARCINOGENICITY:

IARC: No

NTP: No

OSHA: No

#### REPRODUCTIVE TOXICITY:

This product has not been evaluated for reproductive toxicity.

#### TARGET ORGANS:

Eyes and skin.

### SECTION 4 - FIRST AID MEASURES

#### INHALATION:

Remove to fresh air. If difficulty persists, seek medical attention.

#### INGESTION:

Call poison control center immediately. Follow their specific

---

# Franklin International

## MATERIAL SAFETY DATA SHEET

MSDS Name: Ace Multipurpose Floor Covering Adhesive  
MSDS Number: 601135

Revision Date: 061404  
Page Number: 3 of 4

---

Solubility (in water): Miscible  
pH Value: 9.7  
Boiling Range/Point: 212.°F  
Evaporation Rate: Slower than n-Butyl Acetate  
% Volatile: 33.8%  
Specific Gravity: 1.22  
VOC: 15.1 g/l

### SECTION 10 - STABILITY AND REACTIVITY

Stability: This product is stable  
Hazardous Polymerization: Hazardous polymerization will not occur

CONDITIONS TO AVOID:  
Strong acids and strong bases

INCOMPATIBILITY:  
Easily oxidizable materials.

### SECTION 11 - TOXICOLOGICAL INFORMATION

This formulation has a low order of acute and chronic toxicity by all routes of exposure. Prolonged or repeated exposure may cause skin irritation. Direct contact may cause eye irritation.

Exposure to any chemical substance, including those with a low order of toxicity, should be controlled and minimized to avoid harmful effects.

### SECTION 12 - ECOLOGICAL INFORMATION

This formulation has not been tested for environmental effects.

### SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:  
Disposal of this product must comply with all applicable federal, state and local regulations.

CONTAINER DISPOSAL:  
Disposal of this container should comply with all applicable federal, state and local regulations.

### SECTION 14 - TRANSPORT INFORMATION

UN Number	none
UN Pack Group	N/A
UN Class	Nonhaz
ICAO/IATA Class	Nonhazardous
IMDG Class	Nonhazardous
Shipping Name	Nonhazardous

Packaging may not be approved for shipping by air. Please contact Franklin International for further information.

### SECTION 15 - REGULATORY INFORMATION

TSCA (Toxic Substances Control Act Inventory):  
All components of this product are listed on the TSCA inventory except as exempted.

PENNSYLVANIA:  
Hazardous components required to be listed at 1% or more:  
clay; kaolin; 1332-58-7

Non-hazardous components required to be listed at 3% or more:  
hydrocarbon resin mixture; mineral oil 64742-52-5; water 7732-18-5;  
styrene-butadiene latex 9003-55-8

NEW JERSEY:

---