		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0411612
Synpower™ FULL SYNTHETIC SAE 0W-20 MOTOR OIL		Version: 1.1
VV916		

29 CFR 1910.1200 (OSHA HazCom 2012)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : Synpower™ FULL SYNTHETIC SAE 0W-20 MOTOR OIL

### Recommended use of the chemical and restrictions on use

<b>Details of the supplier of the safety data sheet</b>  Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America  SDS@valvoline.com	<b>Emergency telephone number</b> 1-800-VALVOLINE  <b>Regulatory Information Number</b> 1-800-TEAMVAL  <b>Product Information</b> 1-800-TEAMVAL
---	--

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

### GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

### Other hazards

None known.


## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

### Hazardous components


Chemical Name	CAS-No.	Classification	Concentration (%)
HEAVY PARAFFINIC DISTILLATE	64742-54-7	Asp. Tox. 1; H304	69.35

		Page: 2
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0411612
Synpower™ FULL SYNTHETIC SAE 0W-20 MOTOR OIL		Version: 1.1
VV916		

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts	90194-32-4	Eye Irrit. 2A; H319	6.21
--	------------	---------------------	------

#### SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.  
If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.  
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
acne  
stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)
- Notes to physician : No hazards which require special first aid measures.

		Page: 3
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0411612
Synpower™ FULL SYNTHETIC SAE 0W-20 MOTOR OIL		Version: 1.1
VV916		

---

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide  
Hydrocarbons
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---


## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

---

## SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.
- Conditions for safe storage : Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : No materials to be especially mentioned.

		Page: 4
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0411612
Synpower™ FULL SYNTHETIC SAE 0W-20 MOTOR OIL		Version: 1.1
VV916		

---

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

**Engineering measures** : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

### Personal protective equipment

**Respiratory protection** : No personal respiratory protective equipment normally required.

**Eye protection** : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

**Skin and body protection** : Wear as appropriate:  
Safety shoes  
Wear resistant gloves (consult your safety equipment supplier).

**Hygiene measures** : General industrial hygiene practice.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state** : liquid

**Odour** : No data available

**Odour Threshold** : No data available


**pH** : No data available

: No data available

**Boiling point/boiling range** : 626 °F / 330 °C  
(1,013.333333 hPa)  
Calculated Phase Transition Liquid/Gas

**Flash point** : > 390 °F / > 199 °C  
Method: Cleveland open cup

**Evaporation rate** : No data available


		Page: 5
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0411612
Synpower™ FULL SYNTHETIC SAE 0W-20 MOTOR OIL		Version: 1.1
VV916		

Flammability (solid, gas) : No data available  
 Upper explosion limit : 6 %(V)  
 GLP: Calculated Explosive Limit  
 Lower explosion limit : 1 %(V)  
 GLP: Calculated Explosive Limit  
 Vapour pressure : 1.3333333 hPa (20 °C)  
 Calculated Vapor Pressure  
 Relative vapour density : No data available  
 Relative density : No data available  
 Density : 0.843 g/cm<sup>3</sup>  
 Solubility(ies)  
   Water solubility : No data available  
   Solubility in other solvents : No data available  
 Partition coefficient: n-octanol/water : No data available  
 Thermal decomposition : No data available  
 Viscosity  
   Viscosity, dynamic : No data available  
   Viscosity, kinematic : 45.4 mm<sup>2</sup>/s (40 °C)  
 Oxidizing properties : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.  
 Chemical stability : Stable under recommended storage conditions.  
 Possibility of hazardous reactions : Product will not undergo hazardous polymerization.  
 Conditions to avoid : None known.  
 Incompatible materials : Strong oxidizing agents  
 Hazardous decomposition products : carbon dioxide and carbon monoxide

		Page: 6
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0411612
Synpower™ FULL SYNTHETIC SAE 0W-20 MOTOR OIL		Version: 1.1
VV916		

Hydrocarbons

---

## SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion

### Acute toxicity

Not classified based on available information.

#### Components:

HEAVY PARAFFINIC DISTILLATE:

Acute oral toxicity : LD 50 (Rat): > 15 g/kg

Acute dermal toxicity : LD 50 (Rabbit): > 5 g/kg

### Skin corrosion/irritation

Not classified based on available information.

#### Product:

Result: Repeated exposure may cause skin dryness or cracking.

#### Components:

HEAVY PARAFFINIC DISTILLATE:

Result: Mildly irritating to skin

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts:

Result: Not irritating to skin

### Serious eye damage/eye irritation

Not classified based on available information.

#### Product:

Result: Slightly irritating to eyes

Remarks: Expected based on components.

Remarks: Unlikely to cause eye irritation or injury.

#### Components:

HEAVY PARAFFINIC DISTILLATE:

Result: Not irritating to eyes

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts:

Result: Irritating to eyes


### Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

		Page: 7
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0411612
Synpower™ FULL SYNTHETIC SAE 0W-20 MOTOR OIL		Version: 1.1
VV916		

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:**

HEAVY PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks: No data available

**Carcinogenicity:**

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Components:**


HEAVY PARAFFINIC DISTILLATE:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

		Page: 8
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0411612
Synpower™ FULL SYNTHETIC SAE 0W-20 MOTOR OIL		Version: 1.1
VV916		

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

**Persistence and degradability**

**Components:**

No data available

**Bioaccumulative potential**

**Components:**

No data available

**Mobility in soil**

**Components:**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : No data available

**Components:**

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations**

**REGULATION**


ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

**U.S. DOT - ROAD**

Not dangerous goods
---------------------

**CFR\_RAIL\_C**



		Page: 9
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0411612
Synpower™ FULL SYNTHETIC SAE 0W-20 MOTOR OIL		Version: 1.1
VV916		

Not dangerous goods
---------------------

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods
---------------------

**TDG ROAD\_C**

Not dangerous goods
---------------------

**TDG RAIL\_C**

Not dangerous goods
---------------------

**TDG INWT\_C**

Not dangerous goods
---------------------

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods
---------------------

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods
---------------------

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods
---------------------

**MX\_DG**

Not dangerous goods
---------------------


\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

**SARA 311/312 Hazards** : No SARA Hazards

		Page: 10
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0411612
Synpower™ FULL SYNTHETIC SAE 0W-20 MOTOR OIL		Version: 1.1
VV916		

**SARA 313 Component(s)** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Pennsylvania Right To Know**

HEAVY PARAFFINIC DISTILLATE	64742-54-7	50.00 - 70.00 %
HYDROTREATED HEAVY PARAFFINIC BASE OIL	64742-54-7	10.00 - 20.00 %
HEAVY PARAFFINIC DISTILLATE	64742-54-7	5.00 - 10.00 %
Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts	90194-32-4	5.00 - 10.00 %

**New Jersey Right To Know**

HEAVY PARAFFINIC DISTILLATE	64742-54-7	50.00 - 70.00 %
HYDROTREATED HEAVY PARAFFINIC BASE OIL	64742-54-7	10.00 - 20.00 %
HEAVY PARAFFINIC DISTILLATE	64742-54-7	5.00 - 10.00 %
Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts	90194-32-4	5.00 - 10.00 %
LUBRICANT ADDITIVE	Not Assigned	1.00 - 5.00 %


**California Prop 65** Proposition 65 warnings are not required for this product based on the results of a risk assessment.

**The components of this product are reported in the following inventories:**

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL.
- AUSTR : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECL : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : q (quantity restricted)

**Inventories**


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

		Page: 11
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0411612
Synpower™ FULL SYNTHETIC SAE 0W-20 MOTOR OIL		Version: 1.1
VV916		

## SECTION 16. OTHER INFORMATION

### Further information

Revision Date: 07/31/2016

<p><b>NFPA:</b></p>  <p>Special hazard.</p>	<p><b>HMIS III:</b></p> <table border="1"> <tr> <td style="background-color: blue; color: white;"><b>HEALTH</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: red; color: white;"><b>FLAMMABILITY</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: yellow;"><b>PHYSICAL HAZARD</b></td> <td style="text-align: center;"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>1</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>1</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

### NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

### Full text of H-Statements referred to under sections 2 and 3.


H304                      May be fatal if swallowed and enters airways.  
H319                      Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet  
Valvoline internal data including own and sponsored test reports  
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
BEI : Biological Exposure Index  
CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
FG : Food grade  
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

		Page: 12
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0411612
Synpower™ FULL SYNTHETIC SAE 0W-20 MOTOR OIL		Version: 1.1
VV916		

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System